



PPK-645 Field Service Mat

The unique static-dissipative PPK-645 Field Service Mat is designed to easily transport equipment and material. This fabric, featuring a unique multi-layer construction is flexible, non-tacky and color stable. Using this Field Service Mat allows the engineer to fold and set up a workstation anywhere in the plant.

Only available in blue, the PPK-645 Field Service Mat is highly resistant to tearing. The buried conductive layer is the primary path to ground within the structure. Its construction provides the same resistance-to-ground measurements from any point on the material. It also includes a handy storage pouch for miscellaneous accessories.

Specifications

Resistance Rtt:	At 10 volts, 12% RH (Rtt)	10 ⁶ – 10 ⁷ ohms
	At 100 volts, 50% RH (Rtt)	10 ⁶ – 10 ⁷ ohms
Resistance Rtg:	At 10 volts, 12% RH (Rtg)	10 ⁶ – 10 ⁷ ohms
	At 100 volts, 50% RH (Rtg)	10 ⁶ – 10 ⁷ ohms
Min / Max Temperature Range:	-10 to 140 °F (-24 to 60 °C)	
Size:	25½" x 24" (65 cm x 61 cm)	
Storage Pouch Size:	9½" x 7" (24 cm x 17.8 cm)	
Thickness:	~ .015 inches	
Color:	Blue	

©2007 Prostat Corporation. All rights reserved.
Prostat is the registered trademarks of Prostat Corporation in the United States and other countries.

1072 Tower Lane, Bensenville, IL 60106 USA
Phone +1 (630) 238-8883 Fax +1 (630) 238-9717
Web access: <http://www.prostatcorp.com>

Specifications subject to change without notice.
Printed in U.S.A. REV2: 6/20/07