



SureTest and Qube Q007-PGT

Data Sheet

Test Electrical Circuits and provide an ESD ground path to a previously tested receptacle with the Qube

The PGT-61-164 SureTest® Universal Circuit Analyzer now tests circuits INTERNATIONALLY. This patented unit incorporates all the branch circuit testing capabilities you need to effectively test and troubleshoot a branch circuit from 85 – 250 volts, AND 45 – 65 Hz. Simply add the appropriate country plug adapter for use and plug in. It will apply a full 12, 15 or 20 amp load to a circuit for voltage drop measurements.

The Prostat Qube™ replaces expensive electrical ground circuit testers and indicators with a convenient, cost effective means to connect vital ESD controls to grounded electrical outlets. Use the Qube to ground workstations, mats, wrist strap testers, instruments, and other ESD products to an approved pre-tested facility electrical ground. Frequency, GFCI testing and the capability to identify proper wiring in receptacles.





Data Sheet

Specifications for the PGT-61-164 Universal SureTest Circuit Analyzer

General Specifications	
Case Construction	ABS UL 94 V/0/5VA rated
Display Update for Volt	Less than 2.5 times second
Over-Range Indication on all Functions	Display "OL"
Display	128x64 OLED with backlight
Dimensions	6.4" (L) x 3" (W) x 1.4" (D)
Weight	9.4oz (267g)
Accessories	One (1) AC extension cord provided for plug in to outlets
Double Insulation	Instrument has been evaluated and complies with insulation category III, (Overvoltage category III) Pollution degree 2 in accordance with IEC-644. Indoor use
Environment Specifications	
Operating Temperature	32°F to 122°F (0° C to 50° C) at <80% Rh
Storage Temperature	32°F to 122°F (0° C to 50° C) at <80% Rh
Altitude	2000m (6561.7 ft.)
Safety	UL61010B-1, Cat III-300V UL-1436 for AFCI, GFCI & Outlet
Measurement Specifications	All specifications are at 23° C ± 5° C at less than 80% relative humidity Accuracy is stated as ± ((% of range) + (counts)) AC converter is true rms sensing

Specifications for the Q007B Common Point Ground

Dimensions	
Length (in / cm)	2.12 / 5.385
Width (in / cm)	0.9 / 2.286
Depth (in / cm)	0.9 / 2.286
Weight (oz / g)	2.4 / 68
Physical Properties	
Case Material	Fire Retardant ABS
Color	Green
Configuration	3 standard banana jack inputs, Brass Grounding Pin, 2 FR ABS Spades

1072 Tower Lane, Bensenville, IL 60106 USA
Phone +1 (630) 238-8883 Fax +1 (630) 238-9717

www.prostatcorp.com

©2014 Prostat Corporation. All rights reserved. Prostat, Prostat Corporation, Qube and the Prostat logo are trademarks or registered trademarks of Prostat Corporation or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. Complying with all applicable copyright laws is the responsibility of the user. Prostat reserves the right to change, without notice, product offerings or specifications. Printed in U.S.A. REV2: 11/03/14